

# Fluteless Thread Forming Taps

## Class of Fit Recommendations

These tap recommendations will produce the specified class of fit in most applications. Threads produced should be checked with thread plug gages to ensure that the threads meet required specifications. Threads that gage loose or tight may require experimentation with taps of lower or higher pitch diameter limit ("H" or "D" number).

### Machine Screw & Fractional

SIZE	THREADS PER INCH		"H" LIMIT for CLASS of FIT		
	UNC	UNF	2	2B	3B
0	80	—	H2	H3	H2
1	64	—	H2	H3	H2
	—	72	H2	H3	H2
2	56	—	H2	H3	H2
	—	64	H2	H3	H2
3	48	—	H2	H3	H2
	—	56	H2	H3	H2
4	40	—	H3	H5	H3
	—	48	H3	H5	H3
5	40	—	H3	H5	H3
	—	44	H3	H5	H3
6	32	—	H3	H5	H3
	—	40	H3	H5	H3
8	32	—	H3	H5	H3
	—	36	H3	H5	H3
10	24	—	H4	H6	H4
	—	32	H4	H6	H4
12	24	—	H4	H6	H4
	—	28	H4	H6	H4
1/4	20	—	H4	H6	H4
	—	28	H4	H6	H4
5/16	18	—	H5	H7	H5
	—	24	H5	H7	H5
3/8	16	—	H5	H7	H5
	—	24	H5	H7	H5
7/16	14	—	H5	H8	H5
	—	20	H5	H8	H5
1/2	13	—	H5	H8	H5
	—	20	H5	H8	H5
9/16	12	—	H7	H10	H7
	—	18	H7	H10	H7
5/8	11	—	H7	H10	H7
	—	18	H7	H10	H7
3/4	10	—	H7	H10	H7
	—	16	H7	H10	H7

### Metric

SIZE	PITCH	"D" LIMIT for CLASS of FIT	
		4H	6H
M3	0.5	D3	D5
M4	0.7	D4	D6
M5	0.8	D4	D7
M6	1	D5	D8
M8	1.25	D5	D9
M10	1.5	D6	D10
M12	1.75	D6	D11
M14	2	D7	D11
M16	2	D7	D12
M20	2.5	D7	D12